



Shrimp feed extruder machine

Wet type fish feed pellet machine can make fish feed, shrimp feed, crab feed and pet feed in with high quality and large capacity.

It applies conditioner to ripen the ingredients before press feed pellets. The conditioner connect to a boiler, which provide steam to the conditioner, the temperature of steam is 100-150°C, it can ripen the ingredients while kill bacteria and pathogen.

Ingredients from conditioner go to the extruding chamber, in the chamber the screw push the ingredients forward final press out from the molds to get pellets.

The raw material is 60-80 mesh size powder, the final feed is 0.8-12mm diameter pellets, the length can adjust from the cutter.

Shrimp feed extruder machine technical data:

Model	Capacity (t/h)	Main motor(kw)	Feeder motor(kw)	Cutter motor(kw)	Conditioner motor(kw)	Dimension (mm)	Weight (kg)
DSP60	0.18-0.2	15	0.4	0.4	0.75	1780*1250*1300	480
DSP70	0.25-0.30	18.5	0.6	0.6	1.1	2460*1550*1740	940
DSP80	0.35-0.40	22	1.1	0.75	1.5	2650*1450*1750	1000
DSP90	0.50-0.60	37	1.1	1.1	2.2	2600*2100*1900	2000
DSP120	0.70-0.80	55	1.1	1.5	2.2	3200*1950*1900	2200
DSP135	1.0-1.2	75	1.5	2.2	3.0	3750*1980*1800	2500
DSP160	1.8-2.0	90	2.2	2.2	4.0	6600*2800*2330	3800
DSP200	3.0-4.0	132	2.2	3.0	5.5	6600*2900*2350	4500

III. Spare parts

Spare parts for fish feed pellets extruder is: mold, screw, screw turnbuckle, cutter

We will send you one set of spare parts, it include: three molds, two screw, two wearing sleeve, one cutter. Because when only ship the spare parts, the shipping cost will be high, so we would recommend to have some spare parts when you order the machine.



IV. Package & delivery



Contact: Vincent +86 13838336095 (Mobile/WhatsApp/Wechat) Skype:hvincent2012

V. Molds and final pellets



VI. Fish feed pellet line



